

CORRECTED VERSION

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
26 September 2002 (26.09.2002)


PCT

(10) International Publication Number
WO 02/075435 A1

- (51) International Patent Classification?: **G02C 1/02**
- (21) International Application Number: **PCT/IT02/00026**
- (22) International Filing Date: 18 January 2002 (18.01.2002)
- (25) Filing Language: Italian
- (26) Publication Language: English
- (30) Priority Data:
FI01A000044 16 March 2001 (16.03.2001) IT
- (71) Applicant (for all designated States except US): **BOTTEGA D'ARTE IN FIRENZE S.R.L.** [IT/IT]; Via Poggio Bracciolini 9, I-50126 Firenze (IT).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **FORTINI, Fabio** [IT/IT]; Via Carlo del Greco 27/4, I-50141 Firenze (IT).
- (74) Agents: **MANNUCCI, Michele** et al.; c/o UFF. Tecn. Ing. A. Mannucci S.r.l., Via della Scala, 4, I-50123 Firenze (IT).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: RIMLESS FRAME FOR EYEGASSES AND EYEGASSES COMPRISING SAID FRAME



(57) Abstract: The eyeglasses comprise a pair of lenses (3) and a rimless frame with connecting means between the frame and the lenses. The connecting means comprise a set of projections formed by helical windings (5C, 7B) inserted in corresponding holes in the lenses.

WO 02/075435 A1



Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR,
GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent
(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR,
NE, SN, TD, TG).

(48) Date of publication of this corrected version:

1 May 2003

(15) Information about Correction:

see PCT Gazette No. 18/2003 of 1 May 2003, Section II

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— with international search report

RIMLESS FRAME FOR EYEGLASSES AND EYEGLASSES COMPRISING SAID FRAME

DESCRIPTION

Field of the invention

5 The invention relates to a frame for eyeglasses. More specifically, the invention relates to a type of frame known as "rimless", i.e. in which the lenses are not surrounded - neither partially nor totally - by rims. These frames are called "structural lens" systems, because the lenses are a structural component of the assembly formed by the frame and by the lenses.

10 Further, the invention relates to eyeglasses with a rimless frame.

Description of the prior art

Various different types of rimless frames are known in the prior art.

US-A-4,502,765 describes a rimless frame made of three elements, precisely two lateral temples hinged to lens connecting elements, and an
15 intermediate bridge reciprocally connecting the lenses. To connect the bridge to the lenses, the latter are provided with slots, into each of which two pins connected to the bridge are introduced. The assembly consisting of the slots and the pins prevents the reciprocal rotation of the lens and the bridge, while a screw and a nut are used to actually fasten the bridge to the lens. The
20 screw passes through the slot in the lens, between the two pins of the bridge and through a hole made in a portion of the bridge, to which said pins are solidly fastened. This fastening system is particularly complex, due to the high number of elements it comprises. Furthermore, the use of lenses, nuts and the necessary lens protection washers make the frame cumbersome,
25 annoying because it reduces the visual range and aesthetically unappealing.

US-A-5,073,020 describes a rimless frame in which the elements connecting the lenses to the temples and the intermediate bridge are fastened to the lenses by portions of looped wire inserted in slots in the lenses. Fastening should be obtained by effect of elastic compression of the metallic
30 wire loop on the resting plane of the loop. Such compression is obtained by pressing the wire loop in the slot in the lens so that the elastic deformation of the wire generates a retaining force in correspondence with the ends of the

respective slot.

In practice, this fastening system is neither very efficient nor reliable. For this reason, glue is always applied during assembly to stabilize the lenses on the wire of the frame to increase reliability. This makes lens assembly
5 complex and not entirely reliable.

US-A-5,781,270 describes eyeglasses provided with a metallic wire rimless frame. These eyeglasses present a pair of lenses and a frame comprising a pair of elements for connecting the two lenses to a respective pair of temples and an intermediate bridge for reciprocally connecting the
10 lenses. The respective ends of the connecting elements of the two lenses and the temples present helical windings which mate with corresponding circular holes made in the lenses. Similarly, the ends of the wire of the bridge are shaped in the form of helical windings, which are inserted in corresponding holes in the lenses. The connection between lenses and connecting elements
15 and between lenses and intermediate bridge is obtained by means of a screw passing through the helical windings and is fastened by a specially shaped nut. The windings on the connecting elements and the ends of the bridge are dimensioned to be accurately inserted in the respective holes in the lenses, to prevent the movement of the windings inside the hole. The mechanical
20 fastening between frame and lens is obtained, in correspondence of each set of windings, by means of the aforesaid screw and nut. The purpose of the windings is to avoid that the force generated by the screw fastening is released onto the surface of the internal side of the hole in the lens. Despite the higher reliability of the lens connection, this frame presents a number of
25 shortcomings deriving from the high number of elements and the dimensions of the fastening screws and nuts, which reduces the field of vision and makes the frame relatively heavy.

Object and summary of the invention

The object of the invention is the realization of eyeglasses and frames
30 which do not present the aforesaid shortcomings.

Essentially, according to a first aspect of the invention eyeglasses are provided, comprising a pair of lenses and a rimless frame with connecting

means between the frame and the lenses, in which the connecting means comprise projections inserted in correspondence to the holes in the lenses; characteristically the external dimensions of the projections with respect to the dimensions of the corresponding holes form an interference of the projections
5 in the corresponding holes whereby fastening the respective lens to the frame.

In the case of eyeglasses comprising a pair of lenses and a rimless frame, made of metallic wire with connecting means between the frame and the lenses, the connecting means comprise projections in the form of helical
10 metallic wire windings inserted in corresponding holes of the lenses, the external dimensions of the windings with respect to the dimensions of the corresponding holes generating an interference of the windings in the corresponding hole whereby fastening the respective lens to the frame.

In another form of embodiment, the reciprocal intermediate connecting
15 bridge of the lenses and a pair of temples with connecting elements to said respective lenses are made of molded synthetic resin and present projections formed by molding and provided with essentially annular or helical ridges, the ridges generating the interference in the corresponding holes in the lenses.

Unlike the situation described in US-A-5,073,020, the retaining effect is
20 not entrusted to the elastic deformation of a wire loop due to compression in correspondence to the ends of the slots. Conversely, the entire perimetral development of the projections or windings presses on the side of the hole in the lenses. This, on one hand, distributes stress in an optimal way and, on the other hand, reciprocally binds the frame to the lens in a more effective and
25 reliable way. This is because the temples and the bridge of the eyeglasses exert a certain type of stress on the lenses when the eyeglasses are worn. By making the connection between the frame and the lenses either with projections made of synthetic resin or in the form of metallic wire windings, the projections absorb the stress and ensure uniform distribution thereof on the
30 lens. Furthermore, in the case of projections in the form of windings, the deformation of the first winding, consequent to the applied stress, does not compromise the tightness of the lenses, thanks to the presence of other

windings, unlike frames of the known type in which the mating between frame wire and lens is entrusted to a loop portion of the wire.

The frame is made of a lower number of parts, is easier to apply and lighter, also aesthetically, since no screws are used, unlike other known
5 frames (US-A-5,781,270).

In a practical form of embodiment, the frame can comprise a pair of elements connecting the lenses and a respective pair of temples, as well as an intermediate bridge reciprocally connecting the lenses. In this case, the connecting elements present respective ends shaped with said set of helical
10 windings inserted in corresponding holes in the lenses. This fastening system can be used to bind the bridge to the lenses.

The holes in the lenses can be circular and the windings can be circular windings. In this case, a bond should be provided to prevent the rotation of the lenses with respect to the frame, consisting of lateral notches
15 on the edges of the lenses in which portions of metallic wire forming the helical end windings are inserted.

On the other hand, according to a particularly advantageous embodiment of the invention, the holes in the lenses are elongated, i.e. slotted, and correspondingly the windings formed by the metallic wire are also
20 elongated or oblong. In this way, the rotation between lens and frame is prevented simply by forcing the windings into the slots. This avoids the need to make notches along the edge of the lens which is a starting point for cracks. This also increases the flexibility of design of the frame, as will clearly appear in the examples of embodiment described below.

25 To facilitate the introduction of the windings in the holes (either circular or slotted) in the lenses and to ensure a sufficient retaining force between the frame and the lenses at the same time, according to a possible and advantageous embodiment of the invention, the windings have variable dimensions, so that the totality or set of helical windings present an essentially
30 tapered development, or anyhow presenting a reduction in dimensions of some turns of the winding. This forms a lead-in for inserting and forcing the windings in the hole in the lens. Preferably, only one or two terminal windings

with respect to the rest of the winding present a smaller external dimension to facilitate insertion without reducing or compromising the tightness of the lens after assembly. However the possibility that all windings may present the same dimensions is not ruled out.

- 5 When the holes and windings are elongated, the longer axis of the windings and the holes can be horizontally or vertically oriented with respect to the position of the eyeglasses during use. The choice of orienting the longer axis of the slots and consequently of the windings inserted in the slots can be made on the basis of both technical and aesthetic considerations,
10 according to the shape of the lens and consequently the distribution of the material where the slot is made, which must be as close to the edge as possible to prevent interference with the field of vision, but adequately distanced from the edge to prevent excessively weakening the lens.

- According to a different aspect, the present invention also concerns a
15 rimless frame for eyeglasses with connecting means between the frame and the lenses, in which the connecting means comprise projections destined to be inserted in corresponding holes in the lenses, characterized in that the external dimensions of the projections with respect to the dimensions of the corresponding holes generate an interference of the projections in the
20 corresponding holes to fasten the respective lens to the frame.

- According to a possible form of embodiment, the frame is made of metallic wire and presents a set of helical windings intended to be inserted in corresponding holes of the lenses. Characteristically, the external dimensions of the windings generates an interference and compression of the windings in
25 the holes in the lenses for fastening the lenses to the frame.

 The set of helical windings can be used to connect the bridge and/or the connecting elements of the temples to the lenses.

- The connecting elements can be joined to the temples of the frame by means of a hinge, but the possibility is not ruled out that said connecting
30 elements form an extension of a single continuous wire also forming the temples and which is sufficiently flexible to avoid the presence of a hinge.

 Additional advantageous features of the frame and eyeglasses

according to the invention are indicated in the accompanying claims.

Brief description of the drawings

The invention will be better understood by reading the following description reference being made to the accompanying drawing, which show a practical non limiting example of the invention. In the drawing:

figure 1 is a frontal view of a pair of eyeglasses in a first form of embodiment;

figure 2 shows a plan view according to II-II in figure 1;

figure 3 shows an enlarged detail of a connecting area of the bridge to one of the lenses in the frame of figure 2;

figure 4 shows a similar view of figure 3 of a variant embodiment;

figure 5 shows a portion of the eyeglasses in figures 1 and 2 with a slightly modified temple;

figure 5A shows a modification of the eyeglasses in figures from 1 to 5;

figure 6 shows a frontal view of a different embodiment of the eyeglasses according to the invention;

figure 7 shows a perspective view of a portion of the eyeglasses in figure 6;

figure 8 shows a similar view of figure 7 in a variant embodiment;

figure 9 shows a lateral view of a detail of the form of embodiment in figure 7;

figure 10 shows a variant embodiment in a view similar to figure 9;

figures 11 and 12 show a frontal view of an additional embodiment of a pair of eyeglasses and in the view according to XII-XII in figure 11;

figure 13 shows a partial exploded perspective view;

figures 14 and 15 show two local cross-sections according to XIV-XIV and XV-XV in figure 11 (enlarged) and

figure 16 is similar to figure 14 illustrating in this case the trimmed appearance after shortening the joining projection.

Detailed description of the preferred embodiments of the invention

With reference to figures from 1 to 5, numeral 1 generically indicates a pair of eyeglasses comprising lenses 3 and a pair of temples 5. The lenses 3

are reciprocally joined by a bridge 7. The bridge 7 and the temples 5 are made of metallic wire. Pads for resting the eyeglasses on the nose, generically indicated by reference numeral 9 in the view of figure 1 and omitted in the other figures for the sake of simplicity, can be either soldered or
5 fastened in other way to the bridge 7.

In figures 1 and 2, the temples 5 are hinged by means of respective hinges 5B to respective lateral elements 5A connecting the temples to the respective lenses 3. It is not ruled out that the temples 5 can be made of a continuous metallic wire which also forms the lateral connecting element 5A of
10 the lenses, as shown in figures 5 and 5A.

Each of the connecting elements 5A comprises a set of helical windings 5C which, as shown particularly in the view of figure 5, present a tapered (i.e. conical) shape to be more easily inserted with a certain force in circular holes 3A made in the lenses 3. The forcing determines the shape
15 coupling between the connecting element 5A (and more precisely the terminal helical windings 5C) and the respective lens 3.

Since the hole 3A and the windings 5C each present a circular shape, a notch 3B is provided on the edge of each of each lens in which a portion of the metallic wire forming the connecting element 5A or the temple 5 is
20 inserted, to prevent the reciprocal rotation of the connecting element 5A and the respective lens. Rotation can be prevented in the described way, regardless of the configuration of the temple, either with a hinge 5B as shown in figures 1 and 2, or without a hinge, as shown in figures 5 and 5A. The latter show configurations which differ solely in that in one case the windings 5B are
25 inserted in the hole 3A of the respective lens on the side of the lens facing the user while in the other case the insertion is made on the opposite side.

As appears in figures from 1 to 5, also the intermediate bridge 7 is connected to the lenses 3 by means of a similar arrangement. For this purpose, the bridge presents a set of helical windings 7B on both ends, which
30 are inserted in the corresponding holes 3C in the lenses 3. The windings 7B, in the example shown, present a tapered shape, i.e. a dimension which decreases from the proximal to the distal zone, so as the windings 5B of the

connecting elements 5A. This facilitates inserting and forcing the windings 7B in the holes 3C of the lenses 3.

The circular shape of the holes 3C and the corresponding shape of the helical windings 7B requires additional notches 3D in the lenses 3 which
5 engage approximately straight portions of the wire forming the bridge 7, so to prevent the rotation of the lenses 3 with respect to the bridge 7. This is regardless of the direction in which the windings 7B are inserted in the holes 3B, as shown in the two alternatively forms illustrated in figures 3 and 4.

Figures from 6 to 9 show modified embodiment with respect to figures
10 from 1 to 5A. The same reference numerals are used to refer to the same or corresponding parts in the examples of embodiments shown in figures from 1 to 5A.

The substantial difference between the embodiment in figures from 6 to 9 and the embodiment in figures from 1 to 5A is in that the holes 3C in the
15 lenses 3 in the second case are elongated, i.e. slotted, instead of circular. As shown in figures 6 to 9, the slots can be differently oriented with respect to the eyeglasses, and more specifically can be, for example, oriented horizontally (figures 6, 7 and 9) or vertically (figure 8), according to technical and/or aesthetic needs.

Correspondingly, also the helical windings 5B of the connecting
20 element 5A and the helical windings 7B of the bridge 7 have a flat shape, i.e. are essentially elliptical or otherwise elongated to obtain shape coupling in the slots in the lenses 3.

The elongated shape of the holes for inserting the helical windings and
25 the elongated shape of the latter avoids the presence of the notches 3B and 3D on the edges of the lenses 3, which were provided in the previous example of embodiment. This prevents the need to machine the lenses and eliminates a possible starting point for cracks in the lenses.

In both examples of embodiment, the helical windings 5B and 7B could
30 present essentially constant external dimensions, instead of being variable from the distal end to the proximal end to form a lead-in for insertion in the respective holes of the lenses 3. However, the variable dimension of the

windings facilitates assembly of the frame.

Preferably, some terminal windings present reduced dimensions and the remaining windings have larger and constant dimensions.

Figure 10 shows an embodiment in which the windings have radially
5 constant dimensions, with the exception of a partial end winding, whose size is slightly smaller to facilitate insertion in the hole in the lens.

Figures from 11 to 16 show the realization of a pair of eyeglasses 101 similar to the previously illustrated example, but in this case with the frame made of synthetic resin. Reference numeral 103 indicates the lenses,
10 reference numeral 105 the two temples and reference numeral 107 the bridge joining the two lenses. The temples 105 are joined to a connecting element 105A by means of hinges 105B; the elements 105A connect the respective lenses 103. Alternatively, the temples 105 can form a single part with the connecting elements 105A, with a conformation and material permitting the
15 elastic flexion of the temples to close the assembly 103, 107, 103, 107.

The bridge 107 can be equipped with appendixes 109 (figure 13) for resting the eyeglasses on the nose; said appendixes 109 can be made integral the bridge 107 or be reciprocally connected by a union 109A applicable to the bridge 107 by clipping or forcing by means of cooperating
20 holes and pins, as those indicated by reference numerals 109A and 107A. The appendixes 109 can be plastically adapted when cold or hot, according to the user's needs.

According to the example shown in figures from 11 to 16, holes 110 and 112, whose shape is not circular, being preferably elongated in the form
25 of a short slot, are provided in the lenses 103 for connecting the lenses 103, the bridge 107 and the connecting elements 105A; the connecting elements 105A and the bridge 107 present projections 114 and 116, respectively, possibly made by molding of said elements and said bridge; said projections 114, and 116 are developed as appendixes externally equipped with slightly
30 projecting annular ridges 114A and 116A and preferably also present longitudinal holes 114B and 116B; the cross-section of said projections 114 and 116 correspond to the shape of the holes 110 and 112 and the

dimensions ensure that the projections 114 and 116 can be inserted and forced in the holes 110 and 112, thanks to a certain interference of the dimensions of the holes and the projections due to the presence of the external ridges 114A. Also the presence of the longitudinal holes 114B and 116B favors forced clipping of the projections 114 and 116 in the holes 110 and 112. The holes 114B and the 116B are preferably develop from the ends of the projections 114 and 116. The jointing thus obtained ensures the stable assembly of the eyeglasses. The terminal ends of the projections from the lenses can be cut as indicated by reference numeral 114C in figure 16 and if required heated and deformed to additionally stabilize coupling.

The non-circular shape of the holes 110 and 112 and of the transversal cross-sections of the projections 114 and 116 prevents the relative rotation of the lenses and the components of the frame.

The slightly tapered shape of the projections 114 and 116 facilitates insertion of the projections 114 and 116 in the holes 110 and 112 in the lenses and ensures forcing and stability of the joint.

It shall be understood that the drawing only illustrates a practical form of embodiment of the invention which shape and arrangement can vary all comprised within the concept of this invention.

CLAIMS

1. Eyeglasses comprising a pair of lenses and a rimless frame with connecting means between the frame and the lenses, in which the connecting means comprise projections inserted in corresponding holes in
5 the lenses, characterized in that the external dimension of the projections with respect to the dimension of the corresponding holes generates an interference of the projections in the corresponding holes to connect the respective lens to the frame.
2. Eyeglasses according to claim 1, characterized in that said projections
10 present ridges whose development is essentially annular or helical which generate the interference in the corresponding holes in the lenses.
3. Eyeglasses according to claim 1 or 2, characterized in that said projections present decreasing transversal cross-sections from the base of the union with the frame to the end, so to confer a lead-in conformation to the
15 projections to facilitate insertion and forcing into the corresponding holes.
4. Eyeglasses according to at least one of the claims above, characterized in that said holes are elongated in shape and in that said projection present transversal cross-sections of corresponding shape, the coupling between the projections and the holes preventing the rotation of the connecting
20 elements which respect to the lenses.
5. Eyeglasses according to at least one of claims 1 to 4, characterized in that said frame is made of metallic wire and in that said projections are in the shape of helical windings formed by said metallic wire, the external dimension of the windings with respect to the dimension of the
25 corresponding holes generating an interference of the windings in the corresponding hole for binding the respective lens to the frame.
6. Eyeglasses according to claim 5, characterized in that said frame comprises a pair of connecting elements which connect the lenses to a respective pair of temples and an intermediate bridge reciprocally
30 connecting the lenses and in that said sets of helical windings inserted in the corresponding lateral holes in the lenses are made on the terminal ends of the said connecting elements.

7. Eyeglasses according to claim 6, characterized in that said bridge consists of a wire with two ends each provided with a set of windings and in that the lenses each present a respective additional hole in which the corresponding set of windings of the bridge are inserted.
- 5 8. Eyeglasses according to claim 5, 6, or 7, characterized in that at least some of the windings of each set have an external dimension which is variable and increasing from the distal end to the proximal end of said set of windings so to confer to the set of windings a lead-in conformation for insertion and forcing in the respective hole.
- 10 9. Eyeglasses according to claim 5, 6, 7, or 8, characterized in that said holes are elongated and in that said windings present a corresponding elongated conformation, the coupling of said set of windings and said holes preventing the rotation of the connecting elements which respect to the lenses.
- 15 10. Eyeglasses according to one or more of claims 5 to 8, characterized in that the windings are made of a circular cross-section wire, whose diameter is larger than the smaller transversal dimension of the cavity defined inside said windings.
- 20 11. Eyeglasses according to at least one of claims 1 to 4, comprising an intermediate bridge reciprocally connecting the lenses and a pair of temples with connecting elements of said temples to the respective lenses, characterized in that said bridge and said connecting elements are made of molded synthetic resin and present the projections formed by molding with approximately annular or helical ridges generating the interference in
- 25 the corresponding holes in the lenses.
12. Eyeglasses according to claim 11, characterized in that said projections present longitudinal holes originating from the distal end of the projections.
13. Eyeglasses according at least to claim 11, characterized in that each of said projections can be sheared to reduce the part projecting over the part
- 30 of crossed lens.
14. Eyeglasses according at least to claims 1 and 11, characterized in that the bridge presents two contoured appendixes (109) for resting the

eyeglasses on the nose.

15. Eyeglasses according to claim 14, characterized in that said appendixes (109) are connected by a union (109A) and that cooperating pins and seats for the application of said union to the bridge are provided.
- 5 16. A rimless frame for eyeglasses with connecting means between the frame and the lenses, in which the connecting means comprise projections intended to be inserted in corresponding holes in the lenses, characterized in that the external dimension of the projections which respect to the dimension of the corresponding holes generates an interference of the
10 projections in the corresponding holes to connect the respective lens to the frame.
17. Frame according to claim 16, characterized in that said projections present ridges whose development is approximately annular or helical which generate the interference in the corresponding holes in the lenses.
- 15 18. Frame according to claim 16 or 17, characterized in that said projections present decreasing transversal cross-sections from the base of the union with the frame to the end, so to confer a lead-in conformation to the projections to facilitate insertion and forcing into the corresponding holes.
- 20 19. Frame according at least to one of claims 16 to 18, characterized in that said projections are elongated in shape to match holes having a corresponding shape, the coupling between the projections and the holes preventing the rotation of the connecting elements which respect to the lenses.
- 25 20. Frame according at least to one of claims 16 to 19, characterized in that said frame is made of metallic wire, said projections being formed by sets of helical windings, the external dimension of the windings being such as to generate an interference of the windings in said holes for connecting the connecting elements to the lenses.
- 30 21. Frame according to claim 20, characterized in that it comprises a pair of connecting elements to connect the lenses to a respective pair of temples and an intermediate bridge reciprocally connecting the lenses and in that said sets of helical windings insertable in corresponding lateral holes in the

lenses are made on the terminal ends of the said connecting elements.

22. Frame according to claim 21, characterized in that said bridge consists of a wire with two contoured ends each with a set of windings suitable for being inserted in respective holes in the lenses.
- 5 23. Frame according to claim 20, 21, or 22, characterized in that at least some of the windings of each set have an external dimension which is variable and increasing from a distal end to a proximal end of said set of windings so to confer to the set of windings a lead-in conformation for insertion and forcing in the respective holes in the lenses.
- 10 24. Frame according to one of claims 20 to 23, characterized in that said windings present an elongated conformation, the coupling of said set of windings and the holes in the lenses, whose shape is also elongated, preventing the reciprocal rotation of the lenses and the frame.
- 15 25. Frame according to one or more of the claims 20 to 24, characterized in that the windings are made of a circular cross-section wire, whose diameter is larger than the smaller transversal dimension of the cavity defined inside said windings.
- 20 26. Frame according to at least one of the claims 16 to 19, characterized in that it comprises an intermediate bridge reciprocally connecting the lenses and a pair of temples with connecting elements of said temples to the respective lenses, and wherein said bridge (107) and said connecting elements (105) are made of molded synthetic resin and present the projections (116; 114) formed by molding with approximately annular or helical ridges (116A; 114A) generating the interference in the
- 25 corresponding holes (112; 110) in the lenses.
27. Frame according to claim 26, characterized in that said projections present longitudinal holes (114B; 116B) originating from the distal end of the projections.
28. Frame according at least to claim 26, characterized in that each of said
- 30 projections can be sheared to reduce the part projecting over the part of crossed lens.
29. Frame according at least to claim 26, characterized in that the bridge

presents two contoured appendixes (109) for resting the eyeglasses on the nose.

30. Frame according to claim 29, characterized in that said appendixes (109) are connected by a union (105A) and that cooperating pins and seats
5 (107A; 109B) for the application of said union to the bridge are provided.




Fig.1










Fig. 2










Fig.13




Fig.14




Fig.15




Fig.16

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/IT 02/00026

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 G02C1/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 G02C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P, X	EP 1 087 250 A (CARLON ROBERTO ; SINTHESYS S R L (IT)) 28 March 2001 (2001-03-28) column 2, line 58 - column 4, line 34 ---	1, 2, 16, 17
Y	US 6 024 445 A (CONNER BRIAN N ET AL) 15 February 2000 (2000-02-15) column 5, line 31 - line 64 ---	1-4, 11, 16-19, 26
Y	EP 0 863 423 A (MURAI KK) 9 September 1998 (1998-09-09) column 5, line 7 - line 17 column 8, line 41 - column 9, line 4 ---	1-4, 11, 16-19, 26
A	US 5 781 270 A (FORTINI PAOLO) 14 July 1998 (1998-07-14) cited in the application column 1, line 65 - column 2, line 55 ---	1, 2, 5-7, 16, 17, 20-22

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

*** Special categories of cited documents:**

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

Z document member of the same patent family

Date of the actual completion of the international search

29 April 2002

Date of mailing of the international search report

10/05/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

CALLEWAERT, H

INTERNATIONAL SEARCH REPORT

Int. Patent Application No
PCT/IT 02/00026

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	FR 2 715 235 A (TIMON) 21 July 1995 (1995-07-21) claims	1, 4, 16, 19
A	US 5 367 344 A (FUCHS GERHARD) 22 November 1994 (1994-11-22) column 2, line 54 -column 3, line 21	1, 2, 16, 17

Form PCT/ISA/210 (continuation of second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

— information on patent family members

International Application No

PCT/JP 02/00026

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 1087250	A	28-03-2001	IT 80990108 U1 EP 1087250 A1	21-03-2001 28-03-2001
US 6024445	A	15-02-2000	AU 1450100 A BR 9915244 A CN 1325500 T EP 1127289 A1 NO 20012147 A TR 200101221 T2 TW 419072 Y WO 0026716 A1 US 6250755 B1	22-05-2000 24-07-2001 05-12-2001 29-08-2001 04-07-2001 21-08-2001 11-01-2001 11-05-2000 26-06-2001
EP 0863423	A	09-09-1998	EP 0863423 A2 CN 1089038 A DE 69324231 D1 DE 69324231 T2 EP 0611978 A1 GB 2274728 A ,B HK 28797 A WO 9402876 A1 JP 3177214 B2 JP 11064799 A JP 2852814 B2 KR 159580 B1 US 5835183 A	09-09-1998 06-07-1994 06-05-1999 29-07-1999 24-08-1994 03-08-1994 21-03-1997 03-02-1994 18-06-2001 05-03-1999 03-02-1999 01-05-1999 10-11-1998
US 5781270	A	14-07-1998	IT F1940077 U1 IT F1940122 U1 AT 160227 T AT 165172 T AU 1465295 A CN 1141677 A DE 69501036 D1 DE 69501036 T2 DE 69502077 D1 DE 69502077 T2 EP 0772793 A1 EP 0721134 A2 EP 0717301 A2 ES 2109827 T3 WO 9602014 A1 JP 2744851 B2 JP 9507924 T	10-10-1994 17-05-1996 15-11-1997 15-05-1998 09-02-1996 29-01-1997 18-12-1997 12-03-1998 20-05-1998 15-10-1998 14-05-1997 10-07-1996 19-06-1996 16-01-1998 25-01-1996 28-04-1998 12-08-1997
FR 2715235	A	21-07-1995	FR 2715235 A1	21-07-1995
US 5367344	A	22-11-1994	EP 0561763 A1	22-09-1993